

# Technical Data Sheet

## ACTABRITE

### Leafing Aluminium Paste

Product: AB2000-1

Solvent: Mineral Spirit

| Characteristics                              | UOM                | Test Method  | Specification |
|--|--------------------|--------------|---------------|
| <u>Sieve analysis:</u><br>Retention on 45 µm | %                  | ISO-1247     | 5 max         |
| Non volatile matter                          | %                  | ISO-1247     | 65 min        |
| Leafing value                                | %                  | ISO-1247     | 75 min        |
| Water coverage                               | cm <sup>2</sup> /g | ISO-1247     | 25000 typical |
| D50  | µm                 | Malvern-2000 | 22 ± 2        |

AB2000-1 High quality Standard Leafing Aluminium Paste has a specially controlled particle size range in corn flake morphology in mineral spirit as pasting agent. Its controlled particle size, narrow PSD and properly oriented flakes gives smooth finish without protrusion makes the surface smooth to provide strong, high brilliant metallic effects for the applications like Chrome finish coatings, Corrosion protection coatings, Decorative coatings, Exterior coatings with high reflectivity, general purpose coatings, Heat-resistant coatings, Industrial coatings, Screen printings, Roof coating etc.

*The data on this technical information sheet correspond with the current status of our knowledge and experience. The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights. We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process.*

## MEPCO

Thirumangalam,  
Madurai  
PIN: 625706  
Tamilnadu, India  
Phone: + 91 4549 280599  
Fax: +91 4549 281273

E-mail:info@mepco.co.in  
Web:www.mepco.co.in

Edition: 09.03.2019  
Page 1 of 1