

Zinc Dust (Atomized)

Product: CO

Characteristics	UOM	Test Method	Specification
Sieve Analysis		ASTM B-214	
+ 250 μm	%		1.0 max.
- 250 + 45 μm	%		Balance.
- 45 μm	%		35 – 55
Particle Size (Fisher Number)	μm	ASTM B-330	35.0 max.
Chemical Analysis			
Total Zinc	%	M/QA/SOP/076	99.0 min.

M/QA/SOP076 based on ISO 3549

CO Made out of super high grade Zinc ingot of > 99.99 % purity, by air atomization, irregular in shape, used for the applications like Abrasives, Anticorrosive coatings, Chemicals, Coal mining, Diamond tools, Dry cell batteries, Galvanizing, Filler, Fireworks in aerial display/light bluish green color emitted sparklers making, Fungicides, Glass, Hydro electrometallurgical, Industrial greases, Lubricant, Medicines, Oil industries, Paints, Pesticides, Powder metallurgy, Reduction of organic compounds, Sintering, Smelters & Refineries, Textile chemicals Thermo diffusion etc.

The data on this technical information sheet correspond with the current status of our knowledge and experience. The liability for the application and processing of our products lies with the buyer, and he is also responsible for observing any third party rights. We reserve the right to alter any product data as a result of technical progress or further developments in the manufacturing process

MEPCO

Thirumangalam,
Madurai
PIN: 625706
Tamilnadu, India
Phone: + 91 4549 280599
Fax: +91 4549 281273

E-mail: info@mepco.co.in
Web: www.mepco.co.in

Edition: 02.01.2023
Page 1 of 1